



June 9-11, 2013 Austin, Texas



The Premier Event for Professionals in the Forest Products Industry

Liquefaction and Characterization of Bamboo Residues with a Glycerol-based Solvent Using Microwave Energy

Jiulong Xie, Graduate Student

Louisiana State University, Renewable Nature Resources Building, Baton Rouge, LA 70803 USA
xiejiulong@iwcs.com

Chung-Yun Hse, Principal Wood Scientist, USDA, Forest Service, Southern Forest Research Station, Pineville, LA, 71360, USA

Todd F. Shupe, Professor, School of Nature Renewable Resource, Louisiana State University Agricultural Center, Baton Rouge, LA, 70803, USA

Jinqiu Qi, Associate Professor, College of Forestry, Sichuan Agricultural University, Yaan, Sichuan, 625014, PRC

Abstract

American *Phyllostachys pubescens* bamboo was subjected to a liquefaction process conducted in a glycerol/methanol co-solvent using microwave energy. The effect of various liquefaction conditions, such as the ratio of raw material/solvent, liquefaction temperature, reaction time, and ratio of glycerol/methanol were investigated for impact on the residue content and product characterization. The results showed that the minimum residue content was obtained with a raw material to solvent ratio of 1:5. With increased temperature or time, the residue content initially substantially decreased then slightly increased, which indicated that the liquefaction process includes decomposition and recondensation stages. The addition of methanol to glycerol resulted in a higher residue content in the decomposition stage, while in the recondensation stage additional methanol reduced the residue content, indicating that glycerol could be selected as a preferable solvent when liquefaction was conducted under a mild reaction condition. Peaks attributed to the functional groups in hemicellulose and lignin were weak or disappeared in the FTIR spectra of residues from the liquefied bamboo under decomposed conditions, while those in the FTIR spectra of recondensation liquefied residues was intensive. This result indicated that hemicellulose and lignin could easily undergo recondensation in glycerol and sulfuric acid using microwave heating. The cellulose content and crystallinity index of the residue from liquefied wood under decomposed condition was higher than that of the untreated bamboo particles. SEM images showed that the bamboo particles were reduced to small-sized bundles or even single fibers and parenchyma cells. This is consistent with the removal of the FT-IR peaks for the lignin component of the residue, indicating that the lignin was removed.

Keywords: liquefied bamboo residue, glycerol, FTIR, SEM



CONVENTION PROGRAM



JUNE 9-11, 2013 AUSTIN, TEXAS

FPS 67TH INTERNATIONAL CONVENTION AND SWST 56TH INTERNATIONAL CONVENTION



Poster # 46

Study of Chromium(VI) Adsorption and Phenol Adsorption onto Nitrogen-Enriched Activated Carbon from Waste Medium Density Fiberboard

Presenter: Yu Wu, Student, Beijing Forestry University

Xiao-juan Jin, Associate Professor, Beijing Forestry University

Poster # 47

Porositization of Cellulosic Fibers for Activated Carbon

Presenter: Changlei Xia, Graduate Research Assistant, University of North Texas

Sheldon Q. Shi, Associate Professor, University of North Texas

Poster # 48

Liquefaction and Characterization of Bamboo Residues with a Glycerol-Based Solvent Using Microwave Energy

Presenter: Jiulong Xie, Graduate Student, Louisiana State University

Chung-Yun Hse: Principal Wood Scientist, USDA Forest Service, Southern Forest Research Station; Todd F. Shupe, Professor, School of Renewable Natural Resources, Louisiana State University; Jinqiu Qi, Associate Professor, College of Forestry, Sichuan Agricultural University

Poster # 49

Renewable Fiber Kenaf Compare to Sugarcane Composites

Presenter: Bing Yang, Graduate Student, University of North Texas

Sheldon Q. Shi, Associate Professor, Department of Mechanical and Energy Engineering, University of North Texas; Michael Allen; Charles L. Webber; Nandika D'Souza, Professor, Department of Materials Science and Engineering, University of North Texas

Poster # 50

Processing Technology of Laminated Bamboo-Bundle Veneer Lumber and Its Properties

Presenter: Zixuan Yu, International Centre for Bamboo and Rattan

ADVANCES IN WOOD TECHNOLOGY

Poster # 51

Rapid Characterization of Forest Logging Residues Using Near Infrared Spectroscopy

Presenter: Brian Kimberly Via, Director, Forest Products Development Center, School of Forestry and Wildlife Sciences, Auburn University

Gifty Acquah, Student, Auburn University; Oladiran Fasina, Professor, Department of Biosystems Engineering, Auburn University

Poster # 52

Rapid Assessment of Check Development in Veneer Overlays

Presenter: Lech Muszynski, PhD, Oregon State University